

Nitrile Powder Free 400mm— 0,16mm

Powder Free Nitrile Glove



Benefits

- Silky comfort fitting
- Soft & light
- Elastic & yields to hand
- Superior puncture resistance
- Fit with wet & dry grip
- Fingertips textured

Features

- AQL 1.5
- Product is tested according to ASTM & EN testing methods for examination gloves and meet ASTM D6319 & EN 455 Part 1-2-3 EN374-3 international standard requirements

Powder Free: yes **Surface:** Textured **Cuff:** Beaded

Colors:



Size	Palm Width (mm)	Length (mm)
Small	83 - 86	Min. 400
Medium	93 - 96	Min. 400
Large	102 - 105	Min. 400
XLarge	110-115	Min. 400
XXLarge	118-123	Min. 400

Physical Properties	Before ageing	After ageing	Glove Thickness	(Single Wall/mm)
Tensile Strength	Min. 17 MPa	Min 16 MPa	Cuff	0.14
Elongation at break	600%	500%	Palm	0.16
Force at break	6.0 N	6.0 N	Finger	0.18

Inspection Parameter	Defect Description	Inspection Plan	Level	AQL
Dimension	Glove Thickness (Cuff, Palm, Fingers, Width, Length)		S-2	4.0
Physical Properties	Tensile Strength, Ultimate Elongation Force at Brake		S-2	4.0
Visual Inspection	Major Defect, Minor defects		G-1	2.5, 4.0
1000 ml Water Tight Test	Holes, Leaks		G-1	1.5
Powder Free Residue	Powder residue content		N = 5	

Packing Description

Packing	50 pieces per Dispenser, 10 x 50 pieces per Carton
Lot Number Structure	(YYYY = Year of manufacturing, XXX = Julian Day)
Recommended Shelf Life	3 Years upon manufacturing date